



F-4 Series Line Filter

This filter is designed to be used as a standard line filter or it may easily be threaded into a pressure regulator or valve body for inlet protection. If desired we will install this filter for you into any of our standard pressure control valves prior to shipment.

For your special requirements this filter can be custom manufactured of almost any machinable alloy. Let us know your requirement.

Features & Specifications

- Compact Size
- · Economical Design
- Easily Changed Filter Elements
- Stainless Steel Body (316 Series) with Teflon® Seals
- Nominal Micron Ratings of Filtration Available: 10, 20, 50, 70, 100, 200 and 300 Micron
- Pressures Up to 6000 psig

2301 Wardlow Circle Corona, CA 92880 tel 909.270.6200 fax 909.270.6201 www.goreg.com sales@goreg.com

F-4 Series Line Filter

How to Order

Part No. 102120-10

Standard filter with 10 micron nominal filtration

If other than the standard 10 micron filtration is desired, specify by the use of a dash No. For example: 102120-20 for 20 micron filtration or 102120-50 for 50 micron filtration

Maximum Temperature & Control Pressures

Maximum Temperature	@	Maximum Operating Inlet Pressure
500° F (260° C)	@	6000 psiG (41.37 MPa)

Teflon® is a registered trademark of Dupont.

Outline and Mounting Dimensions

